

(2)

AD-A202 927

REPORT DOCUMENTATION PAGE

1b. RESTRICTIVE MARKINGS

DTIC FILE COPY

2a. SECURITY CLASSIFICATION AUTHORITY

DEC 07 1988

2b. DECLASSIFICATION/DOWNGRADING SCHEDULE

3. DISTRIBUTION/AVAILABILITY OF REPORT

Approved for public release;
distribution unlimited.

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

H 80

5. MONITORING ORGANIZATION REPORT NUMBER(S)

ARO 20295.3-PH-F

6a. NAME OF PERFORMING ORGANIZATION

Univ. of Rochester

6b. OFFICE SYMBOL
(If applicable)

7a. NAME OF MONITORING ORGANIZATION

U. S. Army Research Office

6c. ADDRESS (City, State, and ZIP Code)

Institute of Optics
Rochester, NY 14627

7b. ADDRESS (City, State, and ZIP Code)

P. O. Box 12211
Research Triangle Park, NC 27709-22118a. NAME OF FUNDING/SPONSORING
ORGANIZATION

U. S. Army Research Office

8b. OFFICE SYMBOL
(If applicable)

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

DAAG29-83-G-0015

8c. ADDRESS (City, State, and ZIP Code)

P. O. Box 12211
Research Triangle Park, NC 27709-2211

10. SOURCE OF FUNDING NUMBERS

PROGRAM
ELEMENT NO.PROJECT
NO.TASK
NO.WORK UNIT
ACCESSION NO.

11. TITLE (Include Security Classification)

Doctoral Fellowships in Physical Optics

12. PERSONAL AUTHOR(S)

Nicholas George for K. J. Teegarden

13a. TYPE OF REPORT
Final

13b. TIME COVERED

FROM 3/1/88 TO 5/31/88

14. DATE OF REPORT (Year, Month, Day)

November 1988

15. PAGE COUNT

3

16. SUPPLEMENTARY NOTATION

The view, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

17. COSATI CODES

FIELD GROUP SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

Laser Speckle, Cascaded Diffusers, Remote Sensing,
Diffuser Surface Properties.

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

→ The scattering of laser light from a single diffuser and from a cascade of two diffusers is analyzed with particular emphasis on remote sensing. It is shown that diffuser surface properties and the spacing between diffuser planes can be determined remotely. Conceptually, one measures the angular distribution of the radiation pattern or the decorrelation of the far-zone speckle pattern with respect to changes in the wavelength or the angle of incidence of an input plane wave.

20. DISTRIBUTION/AVAILABILITY OF ABSTRACT

☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT. ☐ DTIC USERS

21. ABSTRACT SECURITY CLASSIFICATION

Unclassified

22a. NAME OF RESPONSIBLE INDIVIDUAL

22b. TELEPHONE (Include Area Code)

22c. OFFICE SYMBOL

PROGRESS REPORT

1. ARO PROPOSAL NUMBER: 20295-PH-F
2. PERIOD COVERED BY REPORT: March 1, 1983 to May 31, 1988
3. TITLE OF PROPOSAL: Doctoral Fellowships in Physical Optics
4. CONTRACT OR GRANT NUMBER: DAAG29-83-G-0015
5. NAME OF INSTITUTION: University of Rochester
6. AUTHORS OF REPORT: Nicholas George for K. J. Teegarden
7. LIST OF MANUSCRIPTS SUBMITTED OR PUBLISHED UNDER ARO SPONSORSHIP DURING THIS REPORTING PERIOD, INCLUDING JOURNAL REFERENCES:

This project was successfully terminated on 31 May 1988. The ARO Fellow supported completed his doctoral dissertation during the academic year 1987-88 and an abstract of his thesis is attached.

8. SCIENTIFIC PERSONNEL SUPPORTED BY THIS PROJECT AND DEGREES AWARDED DURING THIS REPORTING PERIOD:

Lyle Shirley, Ph.D., UR - 1988

(now working on remote sensing and ballistic missile decoy discrimination at the MIT Lincoln Laboratories)

Kenneth J. Teegarden
Institute of Optics
University of Rochester
Rochester, NY 14627

LASER SPECKLE FROM THIN AND CASCADED DIFFUSERS

by

Lyle Gordon Shirley

**Submitted in Partial Fulfillment
of the
Requirements for the Degree**

DOCTOR OF PHILOSOPHY

Supervised by Professor Nicholas George

**The Institute of Optics
University of Rochester
Rochester, New York**

Copyright © 1988

ABSTRACT

The scattering of laser light from a single diffuser and from a cascade of two diffusers is analyzed with particular emphasis on remote sensing. It is shown that diffuser surface properties and the spacing between diffuser planes can be determined remotely. Conceptually, one measures the angular distribution of the radiation pattern or the decorrelation of the far-zone speckle pattern with respect to changes in the wavelength or the angle of incidence of an input plane wave.

Models for the transmission of light through single diffusers are presented that contain a dependence on the angle of illumination. The validity of a simplified transmission function for single diffusers that does not depend on angle is examined, and it is found that the simple transmission function is adequate for treating the individual diffusers in a cascade. This is important, since the simpler transmission function leads to manageable overall expressions for the cascade.

A general expression is derived for the two-state correlation function of far-zone complex amplitude from a cascade of two diffusers, where the two states are the initial and final values of the wavelength, angle of incidence, angle of observation, and spacing. This function is then related to the two-state correlation function of intensity, which is a measure of the correlation between the initial and final speckle patterns. The two-state correlation function of intensity is evaluated for various double diffuser combinations.

The effect of surface height models on the radiation pattern is studied. Of particular interest are strong diffusers that have a normally distributed height profile and whose surface height autocorrelation functions are paraboloidal or conical for small spatial offsets. Excellent agreement is obtained between theoretical radiation patterns calculated with conical and paraboloidal autocorrelation functions and experimental radiation patterns measured from ground-glass and acid-etched diffusers, respectively.



n For	
41	<input checked="checked" type="checkbox"/>
	<input type="checkbox"/>
	<input type="checkbox"/>
OR/	
lity Codes	
and/or	
Special	
Dist	
A-1	